EUR5512

EURONET COMPACT BLUE GEL BATTERY – 12V 55Ah

Compact Sealed Gel | UPS, Solar & Emergency Backup



CAPACITY (10HR, 25°C)	NOMINAL VOLTAGE
55Ah	12V
MAX. DISCHARGE (5S)	**INTERNAL RESISTANCE**
550A	≈ 6.8 mΩ
MAX. CHARGE CURRENT	**NET WEIGHT**
13.75A	15kg

OVERVIEW

The EURONET EUR5512 is a compact 12V 55Ah sealed gel battery from the Compact Blue Series, designed for UPS systems, solar storage and emergency backup. It is rated 55Ah at the 10-hour rate to 1.75V/cell at 25°C. GEL-Technology electrolyte gives deep-cycle performance and high charge acceptance, while an internal resistance of about 6.8mΩ supports a 550A (5 sec) peak discharge. The non-spill sealed case needs no water topping, accepts up to 13.75A charge current and works from -40°C to 50°C on discharge.

KEY FEATURES

GEL-Technology Deep Cycle
Advanced gel electrolyte delivers deep-cycle performance and high charge acceptance for solar

550A Peak Discharge
Internal resistance of about 6.8mΩ delivers 550A for 5 seconds for reliable UPS inverter start-up

Solar Deep Cycle
Optimised for PV storage with high charge acceptance and a wide -40°C to 50°C discharge operating range

Maintenance-Free, Non-Spill
Non-spill sealed design needs no water topping and allows flexible mounting in battery cabinets

Wide Temperature Range
Discharge from -40°C to 50°C and charge from -20°C to 50°C, for indoor racks and field installations

Low Self-Discharge
Stores for over 6 months at 25°C, which suits standby and infrequently cycled backup systems

TECHNICAL NOTE

12V, 55Ah @ 10hr to 1.75V/cell at 25°C, 6 cells. Max. discharge 550A (5 sec), internal resistance about 6.8mΩ, max. charge 13.75A. Float 13.50–13.80V, equalisation 14.70–15.00V @ 25°C. Discharge -40°C to 50°C, charge and storage -20°C to 50°C. Terminal T12, net weight 15kg, gross 15.9kg. ABS (UL94-HB) case, UL94-V0 on request. CE, ISO 9001:2015.

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified

EUR5512

PRODUCT TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATIONS
GENERAL	
Model	EUR5512
Series	Compact Blue Series Gel Battery
Battery Type	Sealed gel (GEL-Technology)
Nominal Voltage	12V
Cells Per Unit	6
Rated Capacity	55Ah @ 10hr to 1.75V/cell, 25°C
Applications	UPS, solar storage, emergency backup
ELECTRICAL	
Max. Discharge Current	550A (5 sec)
Internal Resistance	≈ 6.8 mΩ
Max. Charge Current	13.75A
End Voltage	1.75V/cell
CHARGING	
Float Charge	13.50–13.80V @ 25°C
Equalisation	14.70–15.00V @ 25°C

PARAMETER	SPECIFICATIONS
PHYSICAL	
Terminal	T12
Product Dimensions	Not available
Box Dimensions	237 × 142 × 259 mm
Net Weight	15kg
Gross Weight	15.9kg
ENVIRONMENT & LIFE	
Discharge Temperature	-40°C to 50°C
Charge Temperature	-20°C to 50°C
Storage Temperature	-20°C to 50°C
Normal Operating Temp.	25°C ± 5°C
Self-discharge	Storable over 6 months at 25°C
Cycle Life	Not available
CERTIFICATION	
Certifications	CE · ISO 9001:2015
Container	ABS (UL94-HB) · UL94-V0 on request

**Specifications are subject to change without prior notice.*

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified