EUR15012

EURONET BLUE GEL BATTERY – 12V 150Ah

Sealed Deep-Cycle Gel | Solar, UPS & Data Centre Backup



CAPACITY (10HR, 25°C)	NOMINAL VOLTAGE
150Ah	12V
MAX. DISCHARGE (5S)	**INTERNAL RESISTANCE**
1000A	≈ 2.6 mΩ
MAX. CHARGE CURRENT	**NET WEIGHT**
37.5A	44kg

OVERVIEW

The EURONET EUR15012 is a 12V 150Ah sealed deep-cycle gel battery from the Blue Series, built for large-scale solar storage, high-capacity UPS and critical infrastructure backup. It is rated 150Ah at the 10-hour rate to 1.80V/cell at 25°C, with an internal resistance of about 2.6mΩ, a 1000A (5 sec) peak discharge and a 37.5A maximum charge current. The non-spill VRLA design needs no water topping, discharges from -40°C to 50°C and offers up to 2000 cycles at 50% depth of discharge. Its 150Ah capacity suits large off-grid and hybrid solar battery strings.

KEY FEATURES

1000A Peak Discharge
Internal resistance of about 2.6mΩ delivers 1000A for 5 seconds for UPS start-up and heavy loads

37.5A Maximum Charge Current
Charges at up to 37.5A for fast recovery after deep discharge in solar storage and UPS backup systems

Deep Cycle Gel Electrolyte
Advanced gel electrolyte sustains its capacity across repeated deep discharge and recovery cycles

Maintenance-Free VRLA
Non-spill sealed VRLA construction with no water topping or periodic electrolyte service needed

Wide Temperature Range
Discharge from -40°C to 50°C and charge from -20°C to 50°C, for server rooms and outdoor enclosures

Long Cycle & Shelf Life
Up to 2000 cycles at 50% depth of discharge, and stores for over 6 months at 25°C before recharge

TECHNICAL NOTE

12V, 150Ah @ 10hr to 1.80V/cell at 25°C, 6 cells. Max. discharge 1000A (5 sec), internal resistance about 2.6mΩ, max. charge 37.5A. Float 13.50–13.80V, equalisation 14.70–15.00V @ 25°C. Discharge -40°C to 50°C, charge and storage -20°C to 50°C. Terminal T14, net weight 44kg. Up to 2000 cycles @ 50% DoD. ABS (UL94-HB) case. CE, ISO 9001:2015.

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified

EUR15012

PRODUCT TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATIONS
GENERAL	
Model	EUR15012
Series	Blue Series Gel Battery
Battery Type	Sealed VRLA gel, deep cycle
Nominal Voltage	12V
Cells Per Unit	6
Rated Capacity	150Ah @ 10hr to 1.80V/cell, 25°C
ELECTRICAL	
Max. Discharge Current	1000A (5 sec)
Internal Resistance	≈ 2.6 mΩ
Max. Charge Current	37.5A
End Voltage	1.80V/cell
CONSTANT-CURRENT DISCHARGE (TO 1.80V/CELL, 25°C)	
30 Min Rate	119.1 A
1 H Rate	78.4 A
3 H Rate	35.6 A
5 H Rate	24.4 A
10 H Rate	15.0 A
20 H Rate	7.6 A

PARAMETER	SPECIFICATIONS
CHARGING	
Float Charge	13.50–13.80V @ 25°C
Equalisation / Cycle Service	14.70–15.00V @ 25°C
Cycle-use Set Point	2.475V/cell (2.45–2.50V) @ 25°C
Standby Set Point	2.275V/cell (2.25–2.30V) @ 25°C
Max. Charge Current (Cycle)	0.25C
Constant-voltage Charge	14.7–15.0V · 5–11h · max. 0.25CA
Constant-current Charge	0.1CA × 5h
Fast Charge	0.25CA × 1.7h
PHYSICAL	
Terminal	T14
Product Dimensions	Not available
Box Dimensions	485 × 240 × 172 mm
Net Weight	44kg
Gross Weight	44.5kg
ENVIRONMENT & LIFE	
Discharge Temperature	-40°C to 50°C
Charge Temperature	-20°C to 50°C
Storage Temperature	-20°C to 50°C
Normal Operating Temp.	25°C ± 5°C
Cycle Life	Up to 2000 cycles @ 50% DoD
Self-discharge	Storable over 6 months at 25°C
Storage Recharge	At least every 6 months
CERTIFICATION	
Certifications	CE · ISO 9001:2015
Container	ABS (UL94-HB) · UL94-V0 on request

**Specifications are subject to change without prior notice.*

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified