EN-SCP10

EURONET SMART CONTROL PANEL – 10.1"

Android Control Centre | 5MP Camera | Building Intercom



SCREEN **10.1" FHD**	RESOLUTION **1920 × 1200**
OPERATING SYSTEM **Android 11+**	RAM / STORAGE **2GB / 8GB**
CAMERA **5MP + shutter**	PHYSICAL BUTTONS **4 programmable**

OVERVIEW

The EURONET Smart Control Panel 10.1" (EN-SCP10) is the most complete wall panel in the Euronet range, designed for villas, executive suites and lobbies. It runs Android 11 or above on a quad-core 1.8GHz processor and has a 10.1-inch FHD 1920×1200 touch screen. A 5MP camera with physical privacy shutter, temperature, humidity, light and proximity sensors, and a building intercom interface for video intercom, elevator and access control are built in. Zigbee 3.0 and BLE Mesh gateways handle 128+ sub-devices, and it mounts on an 86mm in-wall base or a desktop base.

KEY FEATURES

10.1" FHD Display
1920 × 1200 multi-touch capacitive screen with an anti-fingerprint coating for clear, sharp control

5MP Built-in Camera
Physical privacy shutter covers the 5MP camera when it is not in use, protecting user privacy

Building Intercom
Built-in intercom interface links to video intercom, elevator control and access control systems

Environmental Sensing
Built-in temperature, humidity, light and ToF proximity sensors for intelligent, ambient-aware automation

Custom Buttons
4 programmable physical buttons, each assignable to any device or scene, plus a quick control panel

Wall or Desktop Mount
Fits a standard 86mm in-wall base, or a desktop base with wall bracket for lobby installations

TECHNICAL NOTE

EN-SCP10: 10.1-inch FHD 1920 × 1200 capacitive screen, Android 11 or above, quad-core ARM Cortex-A55 @ 1.8GHz (RK3566), 2GB RAM / 8GB storage. Wi-Fi 2.4GHz, Zigbee 3.0, BLE / BLE Mesh; 128+ sub-devices. 5MP camera with privacy shutter, 2 mics, 2 × 1.8W speakers. Two 10A relays, 2000VA single / 4000VA total load. AC 100V–240V, 50/60Hz. 259 × 161 × 13mm (37mm with base). 0°C to 40°C.

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified

EN-SCP10

PRODUCT TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATIONS
GENERAL	
Model	EN-SCP10
Product Type	Android central control panel and gateway
Operating System	Android 11 or above
App	Euronet IoT App (iOS & Android)
Login	Scan code to authorise
Voice	Online and offline voice control
DISPLAY & CAMERA	
Screen Size	10.1 inch FHD
Resolution	1920 × 1200
Screen Type	Multi-touch capacitive anti-fingerprint coating
Camera	5MP · physical privacy shutter
HARDWARE	
Processor	Quad-core ARM Cortex-A55 @ 1.8GHz
Chip	Rockchip RK3566
RAM / Storage	2GB / 8GB
Microphones	2
Speakers	2 × 1.8W
Physical Buttons	4 programmable (T-Control)
Antennas	3 · built-in shell antenna
SENSORS	
Temperature & Humidity	0–50°C / 0–100% RH · I2C
Light Sensor	I2C · 16-bit digital output
Proximity (ToF)	25° field of view · 0.02–1m

PARAMETER	SPECIFICATIONS
WIRELESS & GATEWAY	
Wi-Fi	2.4GHz
Zigbee	Zigbee 3.0 gateway
Bluetooth	BLE / BLE Mesh gateway
Sub-devices	128+ Zigbee and 128+ BLE/SigMesh
Local Control	LAN device and scene control
OTA Updates	Supported
INTERFACES & RELAYS	
Relays	2 × 10A, 100V–240V
Load	2000VA single / 4000VA total max
Ethernet	1 × 100M RJ45 (not on EU model)
RS485	1 × RS485 (not on EU model)
Intercom	Building intercom, elevator & access control
IP Camera View	Live preview and intercom
POWER	
Power Input	AC 100V–240V, 50/60Hz
Low-voltage Input	12V 1A Type-C
Wiring	Neutral wire required
PHYSICAL & ENVIRONMENTAL	
Dimensions	259 × 161 × 13mm (without base)
With Base	259 × 161 × 37mm
Mounting	86mm in-wall base or desktop base
Back Box	Plastic, JB/T 8593 or >40mm deep
Operating Temperature	0°C to 40°C
Operating Humidity	5–90% RH, non-condensing
Installation	Qualified electrician, mains power off
In The Box	Panel, wall bracket, screws, reset pin, manual
Weight	Not available

**Specifications are subject to change without prior notice.*

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified