EUR 12V 26AH

EURONET VRLA BATTERY – 12V 26Ah

Sealed Lead-Acid VRLA | Maintenance-Free



NOMINAL VOLTAGE	CAPACITY (10HR)
12V	26Ah
MAX DISCHARGE (5 SEC)	**INTERNAL RESISTANCE**
300A	8 mΩ
MAX CHARGING CURRENT	**WEIGHT**
7.8A	8.0 kg

OVERVIEW

The EURONET EUR 12V 26AH is a 12V 26Ah valve-regulated lead-acid (VRLA) battery for solar storage, telecom cabinets and mid-scale standby power. Built for enhanced cycle service in standby and intermittent solar applications. It delivers up to 300A for 5 seconds, with internal resistance of 8 mΩ and a maximum charging current of 7.8A. The sealed, non-spill construction with low-pressure venting needs no water topping, and the ABS (UL94-HB) case is available in UL94-V0 on request. Low self-discharge allows storage for more than 6 months at 25°C.

KEY FEATURES

26Ah Rated Capacity
26Ah rated at the 10-hour rate, with six cells in series for a 12V nominal sealed lead-acid block

High Discharge Current
Delivers up to 300A for 5 seconds, with 8 mΩ internal resistance, for strong current delivery

Maintenance-Free, Non-Spill
No water topping and no acid leakage in any orientation with a low-pressure venting system for safe operation

Solar & Telecom Ready
For solar storage, telecom cabinets and mid-scale standby, built for enhanced cycle service use

Wide Temperature Range
Discharge, charge and storage rated from -20°C to 50°C, with normal operation at 25°C ± 5°C

Low Self-Discharge
Storable for more than 6 months at 25°C, with a recharge before use to restore full capacity

TECHNICAL NOTE

12V, 6 cells per unit, 26Ah at the 10-hour rate. Max. discharge 300A (5 sec), internal resistance 8 mΩ, max. charging current 7.8A. Float charge 13.50-13.80V DC/unit @ 25°C; equalisation & cycle service 14.70-15.00V DC/unit @ 25°C. Discharge -20°C to 50°C; charge and storage -20°C to 50°C; normal operating 25°C ± 5°C. Weight 8.0 kg, terminal T3 / T10, ABS (UL94-HB) container, UL94-V0 on request.

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified

EUR 12V 26AH

PRODUCT TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATIONS
GENERAL	
Model	EUR 12V 26AH
Product Type	Valve-regulated lead-acid (VRLA) battery
Series	VRLA Battery 12V Series
Nominal Voltage	12V
Cells Per Unit	6
Rated Capacity	26Ah @ 10hr rate
Applications	Solar storage, telecom cabinets, mid-scale standby power
Service Type	Standby & intermittent solar cycle service
ELECTRICAL	
Max. Discharge Current	300A (5 sec)
Internal Resistance	8 mΩ
Max. Charging Current	7.8A
CHARGING VOLTAGE (AVERAGE @ 25°C)	
Float Charge	13.50–13.80V DC/unit @ 25°C
Equalisation & Cycle Service	14.70–15.00V DC/unit @ 25°C
Self-discharge	Storable >6 months at 25°C charge before use

PARAMETER	SPECIFICATIONS
PHYSICAL	
Weight	8.0 kg
Dimensions (L × W × H)	Not available
Terminal	T3 / T10
Container Material	ABS (UL94-HB)
Flame Retardancy Option	UL94-V0 on request
TEMPERATURE	
Discharge	–20°C to 50°C
Charge	–20°C to 50°C
Storage	–20°C to 50°C
Normal Operating	25°C ± 5°C
CONSTRUCTION	
Technology	Sealed lead-acid, valve-regulated
Maintenance	Maintenance-free · no water topping
Sealing	Non-spill sealed construction
Venting	Low-pressure venting system
COMPLIANCE	
Marking	CE marked
Manufacturer Quality System	ISO 9001:2015 certified

**Specifications are subject to change without prior notice.*

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified