PUMP SF 2"

EURONET SF SURFACE SOLAR PUMP – 2" 20m³/h

Heavy-Duty DC Engine Pump | No Controller Required



POWER	VOLTAGE
2 HP	DC 150V
MAX FLOW	**MAX HEAD**
20 m³/h	15 m
OUTLET	**SOLAR PANELS**
50 mm	3 × 330 W

OVERVIEW

The EURONET PUMP SF 2" is a heavy-duty DC surface solar pump for high-volume irrigation, water transfer and drainage. Its 2 HP motor runs on DC 150V straight from 3 × 330 W solar panels in series, with no controller needed, and it can also run directly from a battery. It delivers a maximum flow of 20 m³/h and a maximum head of 15 m through a 50 mm (2") outlet, with a working point of 10 m³/h at 10 m head. A 100% copper wire motor, brass impeller and stainless steel screws sit on a portable steel frame with carry handles.

KEY FEATURES

Direct Solar Operation
Runs straight from 3 × 330 W panels in series, with no controller; also runs from a battery

Up to 20 m³/h Max Flow
Maximum flow of 20 m³/h and maximum head of 15 m through a 50 mm (2") outlet for high-volume duty

Rated Working Point
Working head of 10 m at a working flow of 10 m³/h, with flow and head rated at typical operating pressure

100% Copper Wire Motor
Fully copper-wound 2 HP motor drawing 9.5 A on DC 150V for reliable, efficient output

Brass Impeller, S/S Screws
Brass impeller with stainless steel screws for long life in high-volume agricultural pumping

Heavy-Duty Portable Frame
Portable steel frame with carry handles; virtually no maintenance cost and no fuel cost

TECHNICAL NOTE

Model PUMP SF 2" (SF series). Voltage DC 150V, power 2 HP, current 9.5 A. Max head 15 m, max flow 20 m³/h, outlet 50 mm (2"). Working head 10 m, working flow 10 m³/h. PV array 3 × 330 W in series, no controller required; battery operation supported. 100% copper wire motor, brass impeller, stainless steel screws, portable steel frame.

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified

PUMP SF 2"

PRODUCT TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATIONS
GENERAL	
Model	PUMP SF 2"
Series	SF series DC surface pump
Product Type	Engine pump / self-priming
Quality System	ISO 9001:2015 certified
ELECTRICAL	
Voltage	DC 150V
Power	2 HP
Current	9.5 A
Controller	Not required · direct solar connection
Battery Operation	Supported · runs directly from a battery
PV ARRAY	
Solar Panels	3 × 330 W in series
HYDRAULIC PERFORMANCE	
Max Head	15 m
Max Flow	20 m³/h
Working Head	10 m
Working Flow	10 m³/h
Outlet	50 mm (2")
Suction	Not available

PARAMETER	SPECIFICATIONS
CONSTRUCTION	
Motor Winding	100% copper wire
Impeller	Brass
Fasteners	Stainless steel screws
Mounting	Portable steel frame with carry handles
Weight	Not available
OPERATION	
Maintenance	Virtually no maintenance cost easy to operate
Fuel Cost	None · uses free sunlight
Environment	Eco-friendly, non-polluting
APPLICATIONS	
Irrigation	Large-scale field, orchard and row-crop irrigation
Transfer	Agricultural water transfer
Distribution	Farm water distribution networks
Storage	Pond, reservoir and tank filling
Drainage	Drainage management

**Specifications are subject to change without prior notice.*

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified