ACE PRO 2KVA

EURONET ACE PRO UPS – 2000VA / 1200W

Line-Interactive Tower UPS | Built-In AVR



CAPACITY	REAL POWER
2000VA	1200W
INPUT RANGE	TRANSFER TIME
162–290VAC	2–6ms typical
BATTERY	WAVEFORM
12V/9AH ×2	Simulated sine

OVERVIEW

The EURONET ACE PRO 2KVA is a 2000VA / 1200W line-interactive tower UPS for workstations and small networks. Automatic voltage regulation (AVR) boost and buck stabilises power across a wide 162–290VAC input range without draining its two built-in 12V/9AH batteries, and a microprocessor-controlled transfer of typically 2–6ms keeps equipment running through outages. Cold-start and auto-restart allow unattended operation, the batteries recharge to 90% in 4–6 hours, and USB HID enables automatic, safe computer shutdown via management software.

KEY FEATURES

AVR Boost & Buck
Built-in AVR corrects voltage drops and surges across 162–290VAC without draining the battery power

2–6ms Transfer Time
Microprocessor-controlled transfer of typically 2–6ms prevents device crashes and data loss in outages

USB HID Communication
Enables automatic, safe computer shutdown through management software on leading operating systems

Dual Battery Setup
Two built-in 12V/9AH batteries, each 2.5kg, recharge to 90% capacity in 4–6 hours after an outage

Cold Start & Auto-Restart
Starts from battery when mains is absent and restarts automatically, for unattended power recovery

1200W Real Power
2000VA / 1200W supports multiple workstations and small network stacks from a single tower unit

TECHNICAL NOTE

2000VA / 1200W line-interactive tower UPS with AVR. Input 220/230/240VAC, range 162–290VAC. Output ±10% (battery mode), simulated sine wave, typical transfer 2–6ms, PF 1.0. Battery 12V/9AH ×2 (2.5kg each), charging 4–6 hours to 90%. Net weight 11kg, 320×130×182mm, package 390×192×275mm. Noise <45dB, humidity 0–90% RH @ 0–40°C, USB HID.

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified

ACE PRO 2KVA

PRODUCT TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATIONS
GENERAL	
Model	ACE PRO 2KVA
Series	ACE PRO UPS Series
Topology	Line-interactive + AVR
Capacity	2000VA / 1200W
Form Factor	Tower
Applications	Workstations, small networks
INPUT	
Input Voltage	220/230/240VAC
Input Voltage Range	162–290VAC
Voltage Regulation	AVR boost & buck
Generator Compatibility	Supported
OUTPUT	
Output Voltage (Battery Mode)	±10%
Waveform	Simulated sine wave
Transfer Time	Typical 2–6ms
Power Factor	PF 1.0
Output Frequency	Not available
BATTERY	
Battery Type & Quantity	12V/9AH ×2 · built-in
Battery Weight	2.5kg each
Charging Time	4–6 hours to 90% capacity
Battery Management	Cold start · auto-restart

PARAMETER	SPECIFICATIONS
PROTECTION & INTERFACE	
Protection	AVR boost & buck · microprocessor control
Front-panel Indicators	Not available
Communication	USB HID
Management Platform	myEuronet compatible
PHYSICAL & ENVIRONMENTAL	
Dimensions	320×130×182mm
Package Size	390×192×275mm
Net Weight	11kg
Noise Level	<45dB
Humidity	0–90% RH @ 0–40°C
COMPLIANCE	
Certifications	CE · RoHS · ISO 9001:2015

**Specifications are subject to change without prior notice.*

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified