ACE PRO 700VA

EURONET ACE PRO UPS – 700VA / 360W

Line-Interactive Tower UPS | Built-In AVR



CAPACITY	REAL POWER
700VA	360W
INPUT RANGE	**TRANSFER TIME**
140–300VAC	4–8ms typical
BATTERY	**WAVEFORM**
12V/7AH ×1	Simulated sine

OVERVIEW

The EURONET ACE PRO 700VA is a compact line-interactive tower UPS for PCs, workstations and small networking equipment. It provides 700VA / 360W of backup power from one built-in 12V/7AH battery, with a built-in AVR that corrects voltage fluctuations across a 140–300VAC input range without draining the battery. A microprocessor-controlled transfer of typically 4–8ms, a built-in fuse against surges and overloads, cold-start and auto-restart, and USB HID for automatic, safe computer shutdown keep connected equipment protected.

KEY FEATURES

AVR Boost & Buck
Built-in AVR corrects voltage drops and surges across 140–300VAC without draining the battery power

4–8ms Transfer Time
Microprocessor-controlled transfer of typically 4–8ms prevents device crashes and data loss in outages

USB HID Communication
Enables automatic, safe computer shutdown through management software on leading operating systems

Surge & Overload Protection
Built-in fuse shields connected equipment from electrical spikes and sustained overloads at all times

Cold Start & Auto-Restart
Starts from battery when mains is absent and restarts automatically, for unattended power recovery

Compact Tower Design
279×101×142mm tower weighing 4.2kg, with backup outlets, AC input, fuse/breaker and USB port at rear

TECHNICAL NOTE

700VA / 360W line-interactive tower UPS with AVR. Input 220/230/240VAC, range 140–300VAC. Output ±10% (battery mode), simulated sine wave, typical transfer 4–8ms, PF 1.0. Battery 12V/7AH ×1 (1.71kg), charging 4–6 hours to 90%. Net weight 4.2kg, 279×101×142mm, package 324×140×220mm. Noise <45dB, humidity 0–90% RH @ 0–40°C, USB HID.

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified

ACE PRO 700VA

PRODUCT TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATIONS
GENERAL	
Model	ACE PRO 700VA
Series	ACE PRO UPS Series
Topology	Line-interactive + AVR
Capacity	700VA / 360W
Form Factor	Tower
Applications	PCs, workstations, small networking equipment
INPUT	
Input Voltage	220/230/240VAC
Input Voltage Range	140–300VAC
Voltage Regulation	AVR boost & buck
Generator Compatibility	Supported
OUTPUT	
Output Voltage (Battery Mode)	±10%
Waveform	Simulated sine wave
Transfer Time	Typical 4–8ms
Power Factor	PF 1.0
Output Frequency	Not available
BATTERY	
Battery Type & Quantity	12V/7AH ×1 · built-in
Battery Weight	1.71kg
Charging Time	4–6 hours to 90% capacity
Battery Management	Cold start · auto-restart

PARAMETER	SPECIFICATIONS
PROTECTION & INTERFACE	
Surge & Overload	Built-in fuse protection
Rear Panel	Battery backup outlets · AC input fuse/circuit breaker · USB port
Communication	USB HID
Management Platform	myEuronet compatible
PHYSICAL & ENVIRONMENTAL	
Dimensions	279×101×142mm
Package Size	324×140×220mm
Net Weight	4.2kg
Noise Level	<45dB
Humidity	0–90% RH @ 0–40°C
COMPLIANCE	
Certifications	CE · RoHS · ISO 9001:2015

**Specifications are subject to change without prior notice.*

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified