ACE PRO 3KVA

EURONET ACE PRO UPS – 3000VA / 1800W

Line-Interactive Tower UPS | Built-In AVR



CAPACITY	REAL POWER
3000VA	1800W
INPUT RANGE	TRANSFER TIME
162–290VAC	2–6ms typical
BATTERY	WAVEFORM
12V/9AH ×2	Simulated sine

OVERVIEW

The EURONET ACE PRO 3KVA is the highest-capacity line-interactive tower UPS in the ACE PRO range, delivering 3000VA / 1800W for small business workgroups, servers and POS systems. AVR boost and buck regulates power across a 162–290VAC input range without draining its two built-in 12V/9AH batteries, and a microprocessor-controlled transfer of typically 2–6ms keeps loads running. Front-panel LEDs show AC or battery mode, load and battery level and faults, while a circuit breaker protects the input and USB HID handles safe shutdown.

KEY FEATURES

AVR Boost & Buck
Built-in AVR corrects voltage drops and surges across 162–290VAC without draining the battery power

2–6ms Transfer Time
Microprocessor-controlled transfer of typically 2–6ms prevents device crashes and data loss in outages

USB HID Communication
Enables automatic, safe computer shutdown through management software on leading operating systems

LED Status Indication
Front-panel LEDs show AC mode, battery mode, load and battery levels and system faults at a glance

Cold Start & Auto-Restart
Starts from battery when mains is absent and restarts automatically, for unattended power recovery

1800W Real Power
3000VA / 1800W supports dense workgroups, servers, small NAS and POS terminals from a single unit

TECHNICAL NOTE

3000VA / 1800W line-interactive tower UPS with AVR. Input 220/230/240VAC, range 162–290VAC. Output ±10% (battery mode), simulated sine wave, typical transfer 2–6ms, PF 1.0. Battery 12V/9AH ×2 (2.8kg each), charging 4–6 hours to 90%. Net weight 13.6kg, 397×146×205mm, package 490×230×287mm. Noise <45dB, humidity 0–90% RH @ 0–40°C, USB HID.

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified

ACE PRO 3KVA

PRODUCT TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATIONS
GENERAL	
Model	ACE PRO 3KVA
Series	ACE PRO UPS Series
Topology	Line-interactive + AVR
Capacity	3000VA / 1800W
Form Factor	Tower
Applications	Small business workgroups, servers, POS systems
INPUT	
Input Voltage	220/230/240VAC
Input Voltage Range	162–290VAC
Voltage Regulation	AVR boost & buck
Generator Compatibility	Supported
OUTPUT	
Output Voltage (Battery Mode)	±10%
Waveform	Simulated sine wave
Transfer Time	Typical 2–6ms
Power Factor	PF 1.0
Output Frequency	Not available
BATTERY	
Battery Type & Quantity	12V/9AH ×2 · built-in
Battery Weight	2.8kg each
Charging Time	4–6 hours to 90% capacity
Battery Management	Cold start · auto-restart

PARAMETER	SPECIFICATIONS
PROTECTION & INTERFACE	
Input Protection	Circuit breaker
LED Indicators	UPS status · load/battery level · fault
Status Colours	AC mode green battery mode green flashing · fault red
Controls	Power switch
Rear Panel	Output receptacles · AC input circuit breaker · USB comm port
Communication	USB HID
Management Platform	myEuronet compatible
PHYSICAL & ENVIRONMENTAL	
Dimensions	397×146×205mm
Package Size	490×230×287mm
Net Weight	13.6kg
Noise Level	<45dB
Humidity	0–90% RH @ 0–40°C
COMPLIANCE	
Certifications	CE · RoHS · ISO 9001:2015

**Specifications are subject to change without prior notice.*

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified