1500W

EURONET MODIFIED INVERTER (BLUE) – 1500W

Modified Sine Wave Inverter | 12V / 24V DC to 220V AC



RATED OUTPUT POWER	PEAK (SURGE) POWER
1500W	3000W approx.
INPUT VOLTAGE	**OUTPUT**
12V / 24V DC	220V AC ±10%
OUTPUT FREQUENCY	**PEAK EFFICIENCY**
50/60Hz (auto)	90–93%

OVERVIEW

The EURONET Modified Inverter (Blue) 1500W converts 12V or 24V DC battery power into 220V AC ±10% for off-grid solar or wind systems, backup power, vehicles, boats and portable loads. It delivers 1500W continuous and 3000W approx. peak (surge) output, so motor and compressor start-up loads are covered, with automatic 50/60Hz conversion and 90–93% peak efficiency. An LCD shows battery voltage, capacity, output voltage, frequency and load level, and a 5V USB output is built in. A temperature-controlled fan and a full protection suite keep it running safely with lead-acid or lithium batteries.

KEY FEATURES

Surge-Ready Output
1500W continuous with 3000W approx. peak (surge) power from a 12V or 24V battery, for motor start-up

Automatic 50/60Hz
Automatic frequency conversion gives a stable 220V AC at 50Hz or 60Hz for broad appliance compatibility

LCD Display & 5V USB
LCD shows battery voltage, capacity, output voltage, frequency and load level, plus a 5V USB port

Full Protection Suite
Overload, short circuit, over-temperature, battery over/under-voltage and fuse reverse-polarity guard

Smart Thermal Cooling
Intelligent temperature-controlled fan runs only when needed, reducing noise and extending component life

Lead-Acid or Lithium
Works with lead-acid and lithium batteries, with a low-battery alarm and automatic low-voltage cut-off

TECHNICAL NOTE

Rated 1500W, surge 3000W approx. Input 12V / 24V DC, auto (9.6–15.5V / 9.6–30.5V); 220V AC ±10%, 50/60Hz modified sine wave output; efficiency 90–93%. Conversion: 12V mode 80% max / 24V mode 100% max. Battery over/under-voltage, over-temperature, short-circuit and overload protection; fuse reverse polarity. -10°C to 50°C (derate 10% per °C above 40°C), 5–95% RH. Unit 260 × 184 × 88 mm approx.; 3.2 kg approx.

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified

1500W

PRODUCT TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATIONS
GENERAL	
Model	1500W
Series	Modified Inverter (Blue)
Rated Output Power	1500W
Peak (Surge) Power	3000W approx.
Waveform	Modified sine wave
Peak Efficiency	90–93%
Applications	Off-grid solar/wind, vehicle, marine, portable
DC INPUT	
Input Voltage	12V / 24V DC (auto)
Input Range, 12V	9.6–15.5V
Input Range, 24V	9.6–30.5V
Conversion Capability	12V mode 80% max · 24V mode 100% max
Max Continuous, 12V Mode	1200W approx.
DC Input Current, Full Load	110A approx. (12V) · 70A approx. (24V)
AC OUTPUT	
Output Voltage	220V AC ±10%
Output Frequency	50/60Hz, automatic conversion
Waveform	Modified sine wave
USB Output	5V
BATTERY	
Battery Type	Lead-acid or lithium
Low-battery Alarm	Yes
Low-voltage Cut-off	Automatic

PARAMETER	SPECIFICATIONS
PROTECTION	
Battery	Over-voltage and under-voltage
Output	Short circuit and overload
Thermal	Over-temperature
Reverse Polarity	Fuse-protected
Fault Recovery	Auto restart when the fault clears
DISPLAY & COOLING	
Display	LCD
LCD Readings	Battery V, capacity, output V, frequency, load
Cooling	Intelligent temperature-controlled fan
PHYSICAL & ENVIRONMENTAL	
Unit Size	260 × 184 × 88 mm approx.
Packaging Size	29 × 22 × 10 cm approx.
Weight	3.2 kg approx.
Operating Temperature	-10°C to 50°C
Derating	10% per °C above 40°C
Humidity	5–95% RH (non-condensing)
Storage Temperature	-20°C to 55°C
Altitude	Up to 1000m (derate above, GB/T 3859.2)
IP Rating	Not available
CERTIFICATION	
Product	CB, CE, IEC, SASO/SABER
Quality	ISO 9001:2015

**Specifications are subject to change without prior notice.*

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified