EUR6512

EURONET COMPACT BLUE GEL BATTERY – 12V 65Ah

Compact Sealed Gel | UPS, Solar & Emergency Backup



CAPACITY (10HR, 25°C)	NOMINAL VOLTAGE
65Ah	12V
MAX. DISCHARGE (5S)	**INTERNAL RESISTANCE**
650A	≈ 5.3 mΩ
MAX. CHARGE CURRENT	**NET WEIGHT**
16.25A	18.5kg

OVERVIEW

The EURONET EUR6512 is a compact 12V 65Ah sealed gel battery from the Compact Blue Series, designed for solar systems, UPS infrastructure, IT systems and data centre backup. It is rated 65Ah at the 10-hour rate to 1.75V/cell at 25°C. GEL-Technology electrolyte gives deep-cycle performance and high charge acceptance, while an internal resistance of about 5.3mΩ supports a 650A (5 sec) peak discharge. The non-spill sealed case needs no water topping, accepts up to 16.25A charge current and works from -40°C to 50°C on discharge.

KEY FEATURES

GEL-Technology Deep Cycle
Advanced gel electrolyte delivers deep-cycle performance and high charge acceptance for solar

650A Peak Discharge
Internal resistance of about 5.3mΩ delivers 650A for 5 seconds for reliable UPS inverter start-up

Data Centre & Telecom Ready
Designed for solar, UPS, IT systems, data centres, power generation and telecom infrastructure sites

Maintenance-Free, Non-Spill
Non-spill sealed design needs no water topping and allows flexible mounting in battery cabinets

Wide Temperature Range
Discharge from -40°C to 50°C and charge from -20°C to 50°C, for indoor racks and field installations

Low Self-Discharge
Stores for over 6 months at 25°C, which suits standby and infrequently cycled backup systems

TECHNICAL NOTE

12V, 65Ah @ 10hr to 1.75V/cell at 25°C, 6 cells. Max. discharge 650A (5 sec), internal resistance about 5.3mΩ, max. charge 16.25A. Float 13.50–13.80V, equalisation 14.70–15.00V @ 25°C. Discharge -40°C to 50°C, charge and storage -20°C to 50°C. Terminal T14, net weight 18.5kg, gross 19kg. ABS (UL94-HB) case, UL94-V0 on request. CE, ISO 9001:2015.

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified

EUR6512

PRODUCT TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATIONS
GENERAL	
Model	EUR6512
Series	Compact Blue Series Gel Battery
Battery Type	Sealed gel (GEL-Technology)
Nominal Voltage	12V
Cells Per Unit	6
Rated Capacity	65Ah @ 10hr to 1.75V/cell, 25°C
Applications	Solar, UPS, IT, data centres, telecom
ELECTRICAL	
Max. Discharge Current	650A (5 sec)
Internal Resistance	≈ 5.3 mΩ
Max. Charge Current	16.25A
End Voltage	1.75V/cell
CHARGING	
Float Charge	13.50–13.80V @ 25°C
Equalisation	14.70–15.00V @ 25°C

PARAMETER	SPECIFICATIONS
PHYSICAL	
Terminal	T14
Product Dimensions	345 × 180 × 215 mm
Box Dimensions	Not available
Net Weight	18.5kg
Gross Weight	19kg
ENVIRONMENT & LIFE	
Discharge Temperature	-40°C to 50°C
Charge Temperature	-20°C to 50°C
Storage Temperature	-20°C to 50°C
Normal Operating Temp.	25°C ± 5°C
Self-discharge	Storable over 6 months at 25°C
Cycle Life	Not available
CERTIFICATION	
Certifications	CE · ISO 9001:2015
Container	ABS (UL94-HB) · UL94-V0 on request

**Specifications are subject to change without prior notice.*

© 2026 Euronet Technologies LLC. All rights reserved. | ISO 9001:2015 Certified